



## Gateway IoT - Full





## **Overview**






Unlock the power of IoT with IoT Full, a cutting-edge device designed to meet your connectivity and automation needs. Packed with advanced features and built on a foundation of robust specifications, IoT Full is your gateway to a smarter and more efficient future.

At the heart of IoT Full lies the ESP32-WROOM-32E/UE CPU, ensuring lightning-fast data processing and seamless connectivity. With a minimum of 4MB Flash storage, IoT Full offers plenty of room for data storage and firmware updates. It also features multiple communication types such as Wi-Fi, Bluetooth and Ethernet.


IoT Full doesn't shy away from industrial applications. With 1x RS485 Half Duplex port that's ESD protected and supports Modbus RTU, it's your perfect choice for industrial automation and control systems.

IoT Full offers a wide range of digital and analog I/O options, userprogrammable buttons and an RGB LED for easy interaction and status indication, making it a breeze to operate and monitor.

## Physical specification



СРИ	ESP32-WROOM-32E/UE
Memory	520KB SRAM
Storage	At least 4MB Flash
Communication	Wi-Fi 802.11b/g/n 2.4Ghz Bluetooth V4.2 BR/EDR, BLE Ethernet
RS485	1x RS485 Half Duplex ESD protected (Modbus RTU supported)
Digital output	4x relay 10A 240VAC
Digital input	4x optoisolated
Analog output	4x 0-10V
Analog Input	4x configurable (0-20ma, 0-10V, NTC)
NTC input	4x NTC 10k
Groove	1x groove connector + 4 pin terminal block
Button	2x user-programmable button
LED	1x RGB
Power supply	12 to 32Vdc with Polarity Protection
Size	180 x 72 mm



## **IOTREADY S.r.l.**

Via Artigiani, 2 24060 Brusaporto (BG) +39 035 305 3414 hello@iotready.it